

CERTIFICATE OF COMPLIANCE

Certificate Number 20171027-EX16350
Report Reference EX16350-20150618
Issue Date 2017-OCTOBER-27

Issued to: DUYAR VANA MAKINA SAN VE TIC A S
Osmangazi Mahallesi 2653
Sokak No 7, Esenyurt
34522 Istanbul TURKEY

This is to certify that representative samples of SPRINKLERS, AUTOMATIC AND OPEN
See Addendum Page for Models/Product

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL199, Safety for Automatic Sprinklers for Fire Protection Service

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE


Certificate Number 20171027-EX16350
Report Reference EX16350-20150618
Issue Date 2017-OCTOBER-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models/Product:

Automatic sprinklers incorporating a 5mm glass bulb heat responsive element in the following models, types

Listing	SIN	Description	Temperature Ratings, °F
USL	DY3323	Upright 5.6 K, standard response glass bulb style sprinkler plain brass, chrome plated and white painted	135,155,175
USL	DY3327	Pendent 5.6 K, standard response glass bulb style sprinkler plain brass, chrome plated and white painted	135,155,175
USL	DY3423	Upright 5.6 K, quick response glass bulb style sprinkler plain brass, chrome plated and white painted	155
USL	DY3427	Pendent 5.6 K, quick response glass bulb style sprinkler plain brass, chrome plated and white painted	155
USL	DY3329	Horizontal Sidewall 5.6 K, standard response glass bulb style sprinkler plain brass, chrome plated and white painted	135,155,175
USL	DY3429	Horizontal Sidewall 5.6 K, quick response glass bulb style sprinkler plain brass, chrome plated and white painted	155



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

