

Foam hand nozzles with DIN shutoff, without self-education




Our range of low expansion foam hand nozzles without self-education is made of anodised aluminium alloy and red polyester coating. Our hand nozzles are equipped with a "DIN" shutoff allowing to open and close the hand nozzle.

They operate with flow rates ranging from 200 to 800 lpm, and offers connection are possible: BSP or NST-NH threaded, or standardised couplings.



Maximum working pressure: PN16
Material: aluminium alloy
Surface treatment : polyester coated
Shutoff: with ball valve
Carrying handle: 400 and 800 L/min models only
Opening: by lever
Body type: molded
Expansion rate: approx. x10

Inlet	Flow rate (lpm)	Working pressure (bar)	Average range (m)	Dimensions (mm)	Weight (kg)	Ref.
Storz D/25	100	5		430 x 55 x 115	0.8	34836
2" male BSP	200	5	18	502 x 60 x 144	1.2	09049
Storz C/52	200	5	18	533 x 98 x 162	1.5	09050
2" male BSP	400	5	22	646 x 67 x 174	1.7	09051
Storz C/52	400	5	22	678 x 98 x 188	2	09052
Storz B/75	400	5	22	681 x 126 x 202	2.9	09053
2" male BSP	800	5	28	884 x 82 x 217	2.7	09054
Storz B/75	800	5	28	918 x 126 x 217	3.9	09055



Foam hand nozzle with shutoff Gamma "Γ" handle without self-education




Our range of low expansion foam hand nozzles without self-education is made of anodised aluminium alloy and red polyester coating. Our hand nozzles are equipped with a "Gamma Γ" shutoff allowing to open and close the hand nozzle.

They operate with flow rates ranging from 200 to 400 lpm, and various connection are possible: BSP or NST-NH threaded, or standardised couplings.

Maximum working pressure: PN16
Material: aluminium alloy
Surface treatment : polyester coated
Shutoff: with ball valve
Operation: by handle
Body type: molded
Pistol grip : single
Expansion rate: approx. x10

Inlet	Flow rate (lpm)	Working pressure (bar)	Average range (m)	Dimensions (mm)	Weight (kg)	Ref.
2" male BSP	200	5	18	497 x 112 x 242	1.6	15911
2.5" Instantaneous male	225	5	18	608 x 112 x 242	1.9	16065
2" male BSP	400	5	22	705 x 112 x 242	2.4	16067
2.5" Instantaneous male	400	5	22	755 x 112 x 242	2.4	16085



Your ads here
 Information and contact on page 8.